

## CLAIMS

I claim:

1. A method for molding a concrete test cylinder, comprising the steps of:

pouring concrete into a concrete test cylinder mold, said poured concrete extending above a top portion of said concrete test cylinder mold;

placing a cap on said top portion of said concrete test cylinder mold, said cap having at least one excretion hole;

pressing said cap against said top portion of said concrete test cylinder mold, whereby excess concrete is excreted through said excretion hole in said cap;

rotating said cap prior to initial set of said concrete;

curing said poured concrete in said concrete test cylinder mold for a predetermined time; and

removing the cured concrete from said concrete test cylinder mold, whereby a reproducible concrete test cylinder is produced.

2. A method for molding a concrete test cylinder, comprising the steps of:

pouring concrete into a concrete test cylinder mold, said poured concrete extending above a top portion of said concrete test cylinder mold;

placing a cap on top of said concrete test cylinder mold, said cap having at least one radial trough and at least one excretion hole;

EXPRESS MAIL LABEL NO. ET 333675159 US  
I HEREBY CERTIFY THAT THIS PAPER IS BEING DEPOSITED  
WITH THE UNITED STATES POSTAL SERVICE  
EXPRESS MAIL POST OFFICE TO ADDRESSEE SERVICE  
UNDER 37 CFR 1.10 IN AN ENVELOPE ADDRESSED TO:  
ASSISTANT COMMISSIONER FOR PATENTS,  
WASHINGTON, D.C. 20531 ON THIS DATE  
THE COMMISSIONER IS HEREBY AUTHORIZED  
TO CHARGE ANY FEES ARISING HEREFROM AT  
ANY TIME TO DEPOSIT ACCOUNT 50-1037  
8/6/01  
DATE SIGNATURE

rotating said cap, whereby excess concrete is channeled by said radial trough for excretion through said excretion hole in said cap;

rotating said cap prior to initial set of said concrete;

curing said poured concrete in said concrete test cylinder mold for a predetermined time; and

removing the cured concrete from said concrete test cylinder mold, whereby a reproducible concrete test cylinder is produced.

3. Apparatus for molding a concrete test cylinder, comprising in combination:

a concrete test cylinder mold having a top portion; and

a cap having at least one excretion hole positioned on said top portion of said concrete test cylinder mold, whereby excess concrete is excreted through said excretion hole in said cap.

4. The apparatus of claim 3, further comprising:

said top portion of said concrete test cylinder mold having external threads; and

said cap having internal threads for engaging said external threads of said concrete test cylinder mold.

5. The apparatus of claim 3, wherein said cap further comprises at least one handle.

6. Apparatus for molding a concrete test cylinder, comprising in combination:

a concrete test cylinder mold having a top portion; and

a cap having at least one radial trough and at least one excretion hole positioned on said top portion, whereby excess concrete is channeled by said radial trough for excretion through said excretion hole in said cap.

7. The apparatus of claim 6, further comprising:

said top portion of said concrete test cylinder mold having external threads; and

said cap having internal threads for engaging said external threads of said concrete test cylinder mold.

8. The apparatus of claim 6, wherein said cap further comprises at least one handle.